



Flottörfällor - Specifikation

Friflytande flottörfällor (QuickTrap)					
Modell/Serie	Storlek (R, DN)	Material	Tryck (bar)	Max temp (°C)	Max kapacitet (kg/h)
<u>FS3</u>	 R15-25	Rostfritt stål	0.1-21	350°	330
<u>FS5</u>			0.1-32		680

Friflytande flottörfällor (SS Serien)					
Modell/Serie	Storlek (R, DN)	Material	Tryck (bar)	Max temp (°C)	Max kapacitet (kg/h)
<u>SS1N</u>	 R15-25	Rostfritt stål	0.1-21	350°	220
<u>SS1V</u>					330
<u>SS3N</u>			0.1-32		880
<u>SS3V</u>					240
<u>SS5N</u>			0.1-46		240
<u>SS5V</u>					240
<u>SS5NH</u>					240
<u>SS5VH</u>					240

Friflytande flottörfällor (JX Serien)					
Modell/Serie	Storlek (R, DN)	Material	Tryck (bar)	Max temp (°C)	Max kapacitet (kg/h)
<u>J3X</u>	R15-25	Segjärn	0.1-13	200°	720
<u>JF3X</u>	DN15-25				
<u>J5X</u>	R20-40	GGG40.3	0.1-13	200°	1050
<u>JF5X</u>	DN20,25				
<u>JS7X</u>	R25,40	Gjutjärn	0.1-13	200°	3200
<u>J7X</u>	DN20-50				
<u>J7.2X</u>	DN40,50	GG25	0.1-13	200°	9000
<u>J7.5X</u>	DN40-80				15000
<u>J8X</u>	DN50-100				26000

Friflytande flottörfällor (SJ Serien)

Modell/Serie	Storlek (R, DN)	Material	Tryck (bar)	Max temp (°C)	Max kapacitet (kg/h)									
SJ3FNX	DN15-20	Segjärn GGG40.3	0.1-22	220°	950									
SJ3FVX														
SJ5FNX	DN20,25				GGG40.3	0.1-22	220°	1500						
SJ5FVX														
SJ6FNX	DN40,50							GGG40.3	0.1-22	220°	3200			
SJ6FVX														
SJ7FNX														
SJ7FVX														
SJH3NX	DN15										Stål	0.1-32	240°	880
SJH3VX														
SJH5NX	DN20,25													
SJH5VX														
SJH7NX	DN40,45	Stål	0.1-32	240°	4800									
SJH7VX														



Friflytande flottörfällor (JHX Serien)

Modell/Serie	Storlek (R, DN)	Material	Tryck (bar)	Max temp (°C)	Max kapacitet (kg/h)											
JH3X	R15-25 DN15-25	Stål	0.1-32	240°	770											
JHS5X	R15-25 DN15-25															
JHW5X	DN15-25				0.1-32	240°	1050									
JH5X																
JHS7X	R20-40						Stål	0.1-32	240°	4700						
JHW7X	DN20-40															
JH7X	DN40,50									0.1-32	240°	9100				
JHW7.2X																
JH7.2X	DN40-80											0.1-32	240°	15000		
JHW7.5RX																
JH7.5RX	DN50-100													0.1-32	240°	26000
JHW8RX																
JH8RX																



Friflytande flottörfällor (JH Serien)

Modell/Serie	Storlek (R,DN)	Material	Tryck (bar)	Max temp (°C)	Max kapacitet (kg/h)
<u>JH3B</u>	R 15-25 DN15-25	Stål	0.1-32	350°	450
<u>JHS5</u>	R 15-25		400°	0.1-46	920
<u>JHW5</u>	DN15-25				
<u>JH5</u>					
<u>JHS7</u>	R 20-40			0.1-65	4600
<u>JHW7</u>	DN20-40				
<u>JH7</u>					
<u>JHW7.2</u>	DN40,50			0.1-40	15000
<u>JH7.2</u>					
<u>JHW7.5R</u>	DN40-80				
<u>JH7.5R</u>	DN50-100			25000	
<u>JHW8R</u>					
<u>JH8R</u>	DN 100			160000	
<u>JH15-21</u>					
<u>JH15-46</u>					



Friflytande flottörfällor (SH Serien)

Modell/Serie	Storlek (R,DN)	Material	Tryck (bar)	Max temp (°C)	Max kapacitet (kg/h)
<u>SH5NL</u>	DN15-25	Stål	0.1-65	400°	850
<u>SH5NH</u>			0.1-80		250
<u>SH6NL</u>	DN40,50		0.1-32	425°	2100

