

## TLV - Självverkande reglerventiler - Specifikation

### Reducing Valves for Steam

Modell/Serie	Storlek (R,DN)	Material	Tryck (bar)	Max temp (°C)	Press. Adjust. Range (b arg)
<u>COS-3</u>	DN20-50	Järn	1-3	220°	0,1-0,5
<u>COS-16</u>	DN15-100	Järn	2-16		0,3-13,4
<u>COS-16-E</u>	DN15-50	Rostfritt stål	2-16		0,3-13,4
<u>COS-21</u>	DN15-100	Järn	13,5-21		5,5-17,6
<u>SCOS-16</u>	DN15-25	Brons	2-16		0,7-8
<u>COSR-3</u>	DN20-50	Järn	1-3		0,1-0,5
<u>COSR-16</u>	DN15-150	Rostfritt stål	2-16		0,3-13,4
<u>COSR-16-E</u>	DN15-100	Järn	13,5-21		5,5-17,6
<u>COSR-21</u>	DN15-100	Järn	13,5-21		5,5-17,6
<u>SCOSR-16</u>	DN15-25	Brons	2-16		0,7-8



### Namnet

Modell/Serie	Storlek (R,DN)	Material	Tryck (bar)	Max temp (°C)	Press. Adjust. Range (b arg)
<u>DR20</u>	1/2" - 1" DN15 - 25	Stainless Steel	2-16	200°	0.14 – 10



### Surplussing Valves for Steam

Modell/Serie	Storlek (R,DN)	Material	Tryck (bar)	Max temp (°C)	Press. Adjust. Range (b arg)
<u>SP-COSR-16</u>	DN15-50	Järn	21	220°	1-10

